

TECHNICAL DATA



Module/Accessory	Description	Length	Width	Height	Weight	IP Rating	Point Load	Lumen	Ampage	Voltage	Internal Cable Core Size	WARRANTY
Starter Without switch (PTFC00) With switch (PTFCS0)	Connects to a transformer and is the first module in a run of Powertrack.	200mm (not including leads)	258mm	29mm	1.9kg 2.2kg	IP65/IP2X	100kg	n/a	16amp	110v/240v	4mm power / 2.5mm lighting	3 years
Long Runner (PTE120)	Longest connecting module.	1200mm	258mm	29mm	5.7kg	IP65/IP2X	5000kg	n/a	16amp	110v/240v	4mm power / 2.5mm lighting	3 years
Medium Runner (PTE060)	Mid length connecting module.	600mm	258mm	29mm	3.4kg	IP65/IP2X	5000kg	n/a	16amp	110v/240v	4mm power / 2.5mm lighting	3 years
Short Runner (PTE020)	Shortest connecting module.	200mm	258mm	29mm	1kg	IP65/IP2X	5000kg	n/a	16amp	110v/240v	4mm power / 2.5mm lighting	3 years
Lighting (PTLS00WC)	Provides both safety and task lighting 30,00 hours LED life span.	1200mm	258mm	29mm	5.9kg	IP65/IP2X	300kg	2000	16amp	110v/240v	4mm power / 2.5mm lighting	2 years
Emergency Lighting (PTLE00WC)	Emergency enabled luminaire. 30,000 hours LED life span. Emergency back up 1 hour. Battery test and off switch to prevent battery drain down.	1200mm	258mm	29mm	6.2kg	IP65/IP2X	300kg	2000	16amp	110v/240v	4mm power / 2.5mm lighting	2 years
Power (PTPP00)	Power module providing 16amp female commando outlet.	200mm	258mm	29mm	1.6kg	IP65/IP2X	n/a	n/a	16amp	110v/240v	4mm power / 2.5mm lighting	3 years
Power Post (PTPP10)	Slides over top of Power module to avoid creating trip hazard.	86mm	86mm	900mm	0.75kg	n/a	n/a	n/a	n/a	n/a	n/a	3 years
4-Way (PTX000)	Facilitates connections for 4-way direction.	600mm	600mm	29mm	6.7kg	IP65/IP2X	5000kg	n/a	16amp	110v/240v	4mm power / 2.5mm lighting	3 years
Slinky (PTS000)	Provides flexibility to overcome change of levels and planning at any angle.	1000mm	258mm	29mm	3kg	IP65/IP2X	100kg	n/a	16amp	110v/240v	4mm power / 2.5mm lighting	3 years
Braided Slinky (PTSNV0)	This version of our slinky is for sharp changes of direction and is supplied with protective polyurethane braiding along its cabling.	1100mm	258mm	29mm	4.4kg	IP65/IP2X	100kg	n/a	16amp	110v/240v	4mm power + lighting	3 years
Converter - Powertrack to Traditional 110v (PTCM43)	Enables conversion from Powertrack to standard 110v leads.	200mm (not including leads)	258mm	29mm	1.9kg	IP65/IP2X	100kg	n/a	16amp	110v/240v	4mm power / 2.5mm lighting	3 years
Reconverter - Traditional 110v to Powertrack (PTCF43)	Enables conversion back from standard 110v leads to Powertrack.	200mm (not including leads)	258mm	29mm	1.9kg	IP65/IP2X	100kg	n/a	16amp	110v/240v	4mm power / 2.5mm lighting	3 years
Lighting Globe (PTGLSP0) - emergency version also available	Fits onto Power Post and connects to Power outlet to provide 360° light distribution.	n/a	190mm	252mm	1.8kg	IP54	n/a	2600	16amp	110v/240v	n/a	2 years
Test Leads (PTTL02)	Enables electrical testing of modules.	600mm	n/a	n/a	0.4kg	n/a	n/a	n/a	n/a	n/a	1.5mm power + lighting	1 year
Lighting and Power Test Leads (STNTLP)	Enables electrical testing of modules.	400mm	n/a	n/a	0.4kg	n/a	n/a	n/a	n/a	n/a	1.5mm power + lighting	1 year
End Cap (PTEC00)	Protects exposed ends of modules where needed.	150mm	258mm	29mm	0.75kg	IP65/IP2X	500kg	n/a	n/a	n/a	n/a	3 years
T Piece (PTT000)	Facilitates connection for T-arrangement.	600mm	450mm	29mm	5.5kg	IP65/IP2X	500kg	n/a	16amp	110v/240v	4mm power / 2.5mm lighting	3 years
Right / Left Turns (PTTP00)	Facilitates connection for right and left turns.	450mm	450mm	29mm	4kg	IP65/IP2X	500kg	n/a	16amp	110v/240v	4mm power / 2.5mm lighting	3 years